

















-v primeru, da je obstoječ omet prelanek naj se zarezje uitor za horizontalno vez Ø22 v kamnit zlit po izdelavi plošče in sistematičnem injiciranju se Ø22 napne s silo 5 kN.

Pila - specificacija		Ø	l	h	T _h
zon	odlazi iz mreže	[m]	[m]	[m]	[kWh]
1	S240 800	22 800	184 00	434	
2	S240 600	22 650	1 65 19		
3	600	22 630	12 74 4	234	
4	S240 600	22 600	1 60 18	60	
5	S240 500	22 500	1 50 15		
6	S240 350	22 350	1 32 10		
7	S240 270	22 270	1 27 8		
8	S240 170	22 170	1 17 5		
9	780	14 780	4 31 2	39	
10	740	14 740	4 28 6	37	
11	700	14 700	20 14 0	175	
12	670	14 670	4 26 8	34	
13	600	14 600	4 24 0	30	
14	420	14 420	4 16 8	21	
15	400	14 400	2 8 0	10	
16		14 385	2 7 3	9	
17	250	14 235	2 5 9	7	
18	200	14 230	12 30 6	385	
19	200	14 200	12 28 0	333	
20	130	12 600	265 150	1000	
21	600	12 630	5 6 5	8	
22		8 182	31 50 2	21	
23		8 0 53	1730 664	681	
24		8 0 88	17 11 6	5	
25		8 0 82	325 206 5	105	

Pellets - 12/16/18	ϕ [mm]	Tip [in]	Total length [mm]	Total [kg]
	S240 $\phi \geq 12$ mm			
22	169.10	2.98	505	
Shupai (S240, $\phi \geq 12$ mm)			505	
	S500 $\phi \leq 12$ mm			
8	1982.98	0.41	815	
12	1550.00	0.92	1463	
Shupai (S500, $\phi \leq 12$ mm)			2276	
	S500 $\phi > 12$ mm			
14	865.10	1.25	1083	
22	74.40	3.09	230	
Shupai (S500, $\phi > 12$ mm)			1313	
			4066	

16		14	3.65	2	7.3	5
17		14	2.95	2	5.9	7
18		14	2.50	122	306.6	385
19		14	2.60	132	366.0	393
20		14	1.30	5	6.5	8
21		12	6.00	256	1500.0	1466
22		8	1.62	31	50.2	21
23		8	0.93	17.80	67.64	68.68
24		8	0.88	17	11.6	5
25		8	0.82	325	2066.5	105

- 13 kom



MATERIALI:
BETONSKE KONSTRUKCIJE C25/30
zaščina plast betona min. 2,5 cm
ARMATURA BSI 500S

[illegible]